

TX-RZ1100 9.2-Channel Network A/V Receiver



























































Unlock a Seamlessly Immersive Object-Audio Experience

The THX®-certified TX-RZ1100 serves the discerning audiophile with a no-compromises 5.2.4-channel object-based audio experience. This reference receiver is perfect for quad in-ceiling speaker layouts supporting DTS:X® and Dolby Atmos® with mammoth dynamic power to drive front and rear floorstanders. Custom high-current amplification with sophisticated digital noise removal technology delivers stereo and multichannel sound that's nothing short of spectacular. Stream from popular music apps via Chromecast built-in*, DTS Play-Fi®*, AirPlay, and Wi-Fi®; mirror any audio on supported wireless speakers and components via FlareConnect™; and enjoy 4K/60p video supporting BT.2020 and High Dynamic Range (HDR10/Dolby Vision™) passthrough on your main display and 4K/60p video on a second TV via Zone 2 HDMI®. The TX-RZI I 00 is loaded with the A/V and custom home installation technologies you'd expect from a flagship receiver with dynamics that will take your breath away. * Enabled with a firmware update.

HIGHLIGHTS

- 200 W per Channel
- THX® Select2™ Plus Certification
- DTS:X® and Dolby Atmos® to 5.2.4 Channels
- DTS Neural: $X^{\mathsf{\tiny M}}$ Upmixing for Legacy Formats
- Chromecast built-in*¹, DTS Play-Fi^{®*1}, AirPlay, Wi-Fi[®], and Bluetooth[®] Audio Streaming
- AccuEQ Room Calibration with AccuReflex Technology
- FlareConnect^{™*|} Multi-Room Wireless Technology
- HDMI® 8 In (1 Front), Main Out, Zone 2 Out (HDCP 2.2/HDR Pass-through*2)

ADVANCED FEATURES

- THX® Select2™ Plus Cinema-Reference Audio Performance
- 5.2.4-channel DTS:X and Dolby Atmos Object-based Audio Decoding
 DTS Neural:X Upmixes Standard 5.1 and 7.1 formats to 3D Sound
- HDMI Supports 4K/60 Hz, BT.2020, HDR (HDR10/Dolby Vision***)
 Pass-through, 4:4:4 Color Space, and HDCP 2.2-protected Video*2
- Zone 2 HDMI Output Distributes 4K/60 Hz Video to a Second Display
- Chromecast built-in, DTS Play-Fi, Air Play, Wi-Fi, Bluetooth*3, TuneIn, Spotify*, TIDAL*1, and Deezer*1 Audio Streaming*4
- MP3,WMA,WMA Lossless, FLAC, WAV, AAC, and Apple Lossless Playback Over Network and USB
- Network Hi-Res Audio (DSD 5.6 MHz, 192/24 PCM, Dolby® TrueHD)
- Powered Zone 2 and Powered Zone 3 Outputs for Multi-roc Analog and Digital (HDMI/Network/OPT/COAX) Audio with Independent Volume/Tone Controls
- · Whole House Mode
- AccuEQ Calibration with AccuReflex for Seamless Object-based, Multichannel, and Stereo Sound (Setup Mic Included)

- FlareConnect Multi-room Audio Distribution to Compatible
- II.2 Multichannel Pre-Outs for 7.2.4-channel Object-based Audio
- (Separate Stereo Amp Required)

 Onkyo Controller*S App for iOS and Android™ Devices

AMPLIFIER FEATURES

- 200 W/Ch (6 Ω , I kHz, I%THD, I Channel Driven, IEC); 340 W/Ch (6 Ω , I kHz, I0%THD, I Channel Driven, JEITA)
- Onkyo High-Current Digital Amplification for Smooth Low-Distortion Power
- Customized High-Output Transformer, Custom Audio-Grade Capacitors, Separate Transformer for Standby
- Separated Digital and Analog Circuitry to Reduce Interference
- Extruded Metal Heat Sink with Polycarbonate Cooling Fan Optimum Gain Volume Circuitry
- VLSC™ (Vector Linear Shaping Circuitry) Noise-free Signal Processing
- PLL (Phase Locked Loop) Jitter-Cleaning Circuitry for S/PDIF Audio

PROCESSING FEATURES

- HDMI Support for 4K/60 Hz, 3D, Audio Return Channel, DeepColor™, x.v.Color⁶⁷, LipSync, Dolby Atmos, Dolby TrueHD, Dolby⁸ Digital Plus, Dolby⁸ Surround, DTS:X, DTS:HD Master Audio⁻⁷, DTS 96/24, DTS:ES, DTS Express, DTS NeuralX; THX⁹ Cinema/Music/Game, DVD-Audio, Super Audio CD, Multichannel PCM, and CEC
- Dolby Atmos, DTS:X, Dolby TrueHD, and DTS-HD Maste Audio Decoding
- Separate 384 kHz/32-bit AK4490 Stereo DAC (Front L/R)
 2 x 768 kHz/32-bit AK4458 Multichannel DACs (Surround d Channels)
- Discrete 192 kHz/24-bit AK4388 Stereo DACs (x2) for Zone 2 and Zone 3
- Multiple 32-bit Digital Signal Processing Engines
- 4 DSP Modes for Gaming: Rock, Sports, Action, and RPG
 Theater-Dimensional Virtual Surround Function
- · Direct Mode and Pure Audio Mode

CONNECTION FEATURES

- 8 HDMI Inputs (I Front/7 Rear), Main, and Zone 2 Outputs
- Mass Storage Class USB Memory Playback Capability (Rear Input)
- 11.2 Multichannel Pre-Outs and Zone 2/3 Pre-/Line Outs · Zone 2 and Zone 3 Powered Speaker Outputs/Bi-Amping Outputs
- Component Video Switching (2 Inputs and 1 Output) and 2 Composite Video Inputs
- 5 Digital Audio Inputs (3 Optical and 2 Coaxial) and 7 Analog Audio Inputs
- Phono Input (MM) for Turntable Connection
- Dual Subwoofer Pre-Outs
- 12 V Trigger Out (Assignable) with IR Input; Supports IP and RS232
- 6.3 mm Headphone Input

OTHER FEATURES

- Tone Controls (Bass/Treble) ±10 dB for All Channels
- Independent Crossover Adjustment for All Channels (40/50/60/70/80/90/100/120/150/180/200 Hz)
- A/V Sync Control (Up to 500 ms in 5 ms Steps at 48 kHz)
- · New Graphical Overlaid On-Screen Display (OSD) via HDMI with Quick Setup Function
- Hybrid Standby Function with HDMI Passthrough
- 40 FM/AM and 40 Internet Radio Station Presets
- RIHD (Remote Interactive Over HDMI) for System Control
- Aluminum Front Panel and Volume Control Knob
- Simple Remote Control

*! Enabled with a firmware update. *2 6G Videol/HDRJHDCP 2.2 supported on HDMI inputs I-5, Main Out, and Zone 2 Out. *3 Bluetooth specification Version 4.1 (compatible profile A2DP v1.2, ANRCP v1.3) also supporting Advanced Music Optimize. *4 Availability of services objected on region. Some services may require a polar disuscipation and firmware update. Availability of third-party services odvertised here is accurate at the time of publication, but may be subject to change without notice. *5 For 105 and Android" devices. Please check App Store or Google Play for device and OS requirements.

TX-RZ1100 9.2-Channel Network A/V Receiver

A Complete DTS:X® and Dolby Atmos® Experience

Packing 9.2 channels, the TX-RZ1100 unlocks a full 5.2.4-channel Dolby Atmos® and DTS:X experience via four in-ceiling (or up-firing) speakers. Included 11.2 multichannel pre-outs enable 7.2.4-channel layouts (requires stereo amp)



Upmixes Standard Surround Formats

DTS Neural:X™ retrieves spacial cues from standard multichannel formats and upmixes for 3D playback that's virtually identical to a native DTS:X source, giving your existing Blu-ray library a new lease on life.

THX®-Certified for Cinema Reference Sound

THX® Select2™ Plus guarantees distortion-free Cinema Reference Volume in your home. Certified products are subjected to the industry's toughest bench-tests to satisfy THX requirements for audio performance.

Onkyo High-Current Digital Amplification

The TX-RZII00 combines high-current driving architecture with sophisticated digital amplification and filtering technology.

Noise-reduction hardware including a custom high-output transformer delivers fast dynamics, thrilling power, and stunningly precise detail resolution. Painstakingly tuned for velvet-smooth and emotionally evocative audio reproduction, Onkyo High-Current Digital is where power meets control.



Cohesive Multidimensional Sound

AccuReflex—part of the AccuEQ room calibration suitephase-matches Dolby Atmos-enabled and floor-standing speakers for seamless reproduction of object-based sound. AccuEQ optimizes the system to suit your space without affecting front-speaker characteristics for pure stereo listening.





Chromecast built-in*, DTS Play-Fi®*, AirPlay, Wi-Fi®, and Bluetooth®

Popular smartphone and PC music apps let you mirror what's playing to your TX-RZI I 00 with ease using Chromecast built-in and DTS Play-Fi. The receiver also features AirPlay, Bluetooth, and Wi-Fi for universal wireless audio support. * Enabled with a firmware update

Spotify®, Deezer, TIDAL, and TuneIn

Enjoy any music you want on your home cinema via these popular smartphone and PC applications or via Onkyo Controller.

FlareConnect[™] Wireless Multi-room Audio

FlareConnect* shares audio from network and external audio input sources between compatible components. Enjoy effortless multi-room playback of LP records, CDs, network music services, and more with supported components and speaker systems. Music selection, speaker grouping, and playback management across the home are built into the Onkyo Controller** app.



Sharing audio from external inputs is enabled with a future firmware update. external audio inputs supporting FlareConnect may differ depending on model. lease consult individual product specification for more information. free from the App Store or Google Play.

Housewide Playback of Any Source

Put extra speakers you have to good use—connect them to the receiver's Powered Zone 2 and Powered Zone 3 outputs. Dedicated DACs and smartphone control let you manage content in any zone.

Latest Dual-Zone HDMI®

Select HDMI terminals support HDR (HDR10/Dolby Vision™*) pass-through, 4:4:4 color-space, BT.2020, and HDCP 2.2 for next-generation Ultra HD Blu-ray, streaming 4K video, and 4K/60 Hz PC-based gaming. Zone 2 output transmits 4K home cinema sources to a second TV.

* Enabled with a firmware update

SPECIFICATIONS

Power Output	
All Channels	200 W/Ch (6 Ω, 1 kHz, 1%THD,
	I Channel Driven, IEC)
	340 W/Ch (6 Ω, I kHz, 10% THD,
	I Channel Driven, JEITA)
Dynamic Power	320 W (3 Ω, Front)
,	270 W (4 Ω, Front)
	160 W (8 Ω, Front)
THD+N (Total Harmon	ic Distortion + Noise)
	0.04% (1 kHz, 100 Ŵ)
Input Sensitivity and Imp	pedance
	200 mV/82 kΩ (Line)
	3.5 mV/47 kΩ (Phono MM)
Rated RCA Output Lev	
·	I.0 V/330 Ω (Pre Out)
	I.0 V/330 Ω (Subwoofer Pre Out)
	200 mV/1.2 kΩ (Zone Out)
	2.0 V/1.2 kΩ (Zone Pre Out)
Phono Overload	70 mV (MM, I kHz, 0.5%)
Tone Control	+10 dB, 100 Hz (Bass)
	±10 dB, 10 kHz (Treble)
Signal-to-Noise Ratio	108 dB (Line, IHF-A)
	90 dB (Phono MM, IHF-A)
Speaker Impedance	4 Ω – 16 Ω

Tuning Frequency Range

Input Sensitivity/Output Level and Impedance			
Video	I.0 Vp-p/75 Ω (Component Y)		
	0.7 Vp-p/75 Ω (Component PB/CB, PR/CR)		

Tuner Section	
•••••	I.0Vp–p/75 Ω (Composite)
	0.7 Vp-p/75 Ω (Component PB/CB, PR/CR

87 5 MHz_108 MHz

	87.5 MHz-107.9 MHz (Taiwan N
AM	530 kHz-1,710 kHz
	522 kHz-1,611 kHz
	522 kHz-1.611 kHz (Taiwan Mo

General	
FM/AM Preset Memory	
	522 kHz-1,611 kHz (Taiwan Model)


Power Supply	AC 220-230 V~, 50/60 Hz
	AC 120V~, 60 Hz (Taiwan Model)
Power Consumption	320 W
Standby Power Consumption	
	0.15 W
Dimensions (W x H x D) 435 × 201 × 453 mm
Weight	19.7 kg

CARTON

	565 x 325 x 547 mm
Weight	22.5 kg

Supplied Accessories

- Indoor FM antenna AM loop antenna Speaker setup microphone Instruction manual Remote controller AA (R6) batteries \times 2^*
- * Batteries not included with Chinese model variants



Due to a policy of continuous product improvement, Onlyo reserves the right to change specifications and appearance without notice. THX the THX logo, and Select2 are trademarks of THX Ltd THX and the THX logo are registered in the U.S. and other jurisdictions, All rights reserved that the Symbol Degether, DTS, the DTSX logo, Play-Fi, and the Play-Fi logo are registered trademarks or of only or Corporation. All other trademarks are the property of their respective holders.

