



SX-20DAB-K



SX-20DAB-S

DESIGN & BUILD

- › Analogue Discrete 2ch Amplifier
- › DAB/DAB+ Tuner
- › FM Tuner (30 Presets) with RDS Function
- › Phono Input (MM)
- › Speaker A/B Selector
- › Two-Digit FL Display
- › Aluminium Front Panel
- › Sleep Timer
- › Auto Power Down

AMPLIFIER SECTION

- › Rated Power Output
100 W + 100 W (20 Hz-20 kHz, THD 1 %, 8 ohms)

AUDIO SECTION

- › Frequency Response
SACD/CD, NETWORK, RECORDER: 5 Hz-100 kHz, 0 dB/-3 dB
- › RIAA Deviation
PHONO (MM): 20 Hz-20 kHz, ±0.5 dB
- › Tone Control
Bass: ±14 dB (100 Hz)
Treble: ±14 dB (10 kHz)
- › Signal-to-Noise Ratio (IHF SHORTED, A-NETWORK)
SACD/CD, NETWORK, RECORDER: 100 dB
PHONO (MM): 80 dB
- › Total Harmonic Distortion
SACD/CD, NETWORK, RECORDER: 0.02 % or less (1 kHz, 50 W, 8 ohms)

TUNER SECTION

- › Frequency Range (FM): 87.5-108 MHz
- › Frequency Range (DAB): 174.928-239.200 MHz
- › Antenna Input (FM/DAB): 75 ohms unbalanced

TERMINALS

- › Analogue Audio Input: 4 (Phono MM, SACD/CD, NETWORK, RECORDER)
- › Analogue Audio Output: 1 (REC OUT)
- › FM/DAB Tuner Antenna
- › Large Speaker A/B Terminals
- › Speaker Impedance: 4-16 ohms (A or B), 8-16 ohms (A+B)
- › Phones Output
- › AC Inlet

ACCESSORIES

- › Remote control: 1
- › AAC/IEC R03 Dry Cell Batteries: 2
- › FM/DAB Wire Antenna: 1

SPECIFICATIONS

- › Power Requirements: AC 220-230 V, 50/60 Hz
- › Power Consumption in Use/in Standby: 210 W/0.3 W
- › Dimensions (W x H x D): 435 x 142.5 x 364 mm
- › Weight (without Package): 8.3 kg

REAR PANELS



SX-20DAB-K



SX-20DAB-S

DAB+ RDS

PIONEER and the Pioneer logo are registered trademarks of Pioneer Corporation, and are used under license.
 The 'DAB digital radio' logo, the 'digital radio' logo and the stylised 'r' mark © and © Digital One Limited

© 2015 Onkyo & Pioneer Corporation. All rights reserved.
 Note: Specifications and design subject to change without notice.